

NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH POUND

MIL-PRF-39016/14D  
AMENDMENT 1  
10 July 1992

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, 4PDT  
LOW LEVEL TO 2 AMPERES (0.150-INCH TERMINAL SPACING)

This amendment forms a part of MIL-R-39016/14D, dated 20 July 1988 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Requirements, contact data, load ratings, high level (relay case grounded), resistive: Delete "400 Hz life test not required for qualification testing."

CONCLUDING MATERIAL

Custodians:

Army - ER  
Navy - EC  
Air Force - 85

Preparing activity:

Navy - EC

Agent:

DLA - ES

Review activities:

Army - AR  
Navy - AS, OS, SH  
Air Force - 99  
DLA - ES

(Project 5945-0896 03)

User activities:

Navy - MC  
Air Force - 19

INCH-POUND

MIL-R-39016/14D  
AMENDMENT 1  
10 July 1992

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, 4PDT,  
LOW LEVEL TO 2 AMPERES (0.150-INCH TERMINAL SPACING)

This amendment forms a part of MIL-R-39016/14D, dated 20 July 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Requirements, contact data, load ratings, high level (relay case grounded), resistive: Delete "400 Hz life test not required for qualification testing."

CONCLUDING MATERIAL

Custodians:

Army - ER  
Navy - EC  
Air Force - 85

Review activities:

Army - AR  
Navy - AS, OS, SH  
Air Force - 99  
DLA - ES

User activities:

Navy - MC  
Air Force - 19

Preparing activity:

Navy - EC

Agent:

DLA - ES

(Project 5945-0896-03)